



Quality beyond Innovation

Philippine SkyBird Industrial Corp.

31-B, SEB Commercial Center, Ortigas Ave., Taytay, Rizal

Tel: (02) 8693-6560 • (02) 8359-0365 • Website: www.philskybird.com

REFORM MOB

Oil based form release agent for all types of concrete formworks

DESCRIPTION

ReForm MOB is a ready to use oil-based form release agent. It reacts chemically with the cement paste in contact with treated formwork to form a “bond breaking” film which enables the formwork to be readily stripped.

USES

ReForm MOB can be used for steel, wooden or plastic forms in precast industry, high performance durable concrete, architectural finishes, molds with intricate shapes, etc.

ADVANTAGES

- Spray or roller applied
- Ready to use
- Produces high quality concrete surfaces
- Quick and easy release
- Excellent coverage
- Reduce air pockets and tendency for surface spalling at corners
- Does not stain concrete surfaces

TYPICAL PROPERTIES at 25°C

Form	liquid
Color	yellowish
Density 20°C	1.0± 0.02

SURFACE PREPARATION

Molds must be dry, clean, free of rust and foreign matter prior to the application of **ReForm MOB**. Any surface repairs done with putty should be totally cured and dry. Molds should be protected from rain during application.

APPLICATION

ReForm MOB is ready to use and should be applied by spray or roller in a thin even film. If any ponding of mold oil occurs, it should be removed by sponge before mold is used.

PACKAGING

ReForm MOB is available in 20 ltr and 210 ltr drum

COVERAGE

20-30 m²/ltr/coat (coverage depends on surface finish, porosity and texture of molds)

GENERAL INFORMATION

Shelf Life 12 months from date of manufacture when stored under warehouse conditions in original unopened packing. Extreme temperature/humidity may reduce shelf life.

HEALTH and SAFETY

Gloves, goggles & suitable mask must be worn.

TECHNICAL SERVICE

Philippine SkyBird Industrial Corp. Services are available on request for on-site support to assist in the correct use of its products.

