

Philippine SkyBird Industrial Corp.

31-B, SEB Commercial Center, Ortigas Ave., Taytay, Rizal Tel: (02) 8693-6560 • (02) 8359-0365 • Website: www.philskybird.com

ULTRACURE AB

Acrylic Based Concrete Curing

DESCRIPTION

UltraCure AB is a ready-to-use, milky-white liquid, membrane type curing compound for protecting fresh concrete against over rapid water evaporation. It conforms to ASTM C309-80 Type 2 requirements.

USES

- curing compounds on large horizontal or inclined surfaces
- surfaces with specifications for a high degree of water retention

ADVANTAGES

- retains moisture in the fresh concrete
- protects concrete surface against sun, wind and rain
- Paintable
- single coat application
- solvent free
- effective under any temperature and humidity conditions
- prevent rapid evaporation
- reduced shrinkage cracks
- increased mechanical strengths
- easy application thus saving labor and money

UltraCure AB forms a visible coat that is impervious to water vapour and weather. The application of **UltraCure AB** on "green" concrete produces an impervious, white film that retains over 90% of the water in the concrete for at least 3 days. As a result, the finished concrete has a harder, dust-free surface and drying/shrinking cracks are reduced to a minimum. Depending on weathering and/or attrition, the film will be degraded within 3-4 weeks. By that time, hydration will be virtually completed.

TYPICAL PROPERTIES at 25°C

Form viscous liquid Color Milky white Density 20° C 1.0 ± 0.02

MIXING

No mixing is required

METHODS OF USE

Apply UltraCure AB as evenly as possible to the freshly poured concrete. If forms are used, apply it as soon as they are stripped. Do not spray UltraCure AB onto surface-dry concrete. If the concrete has lost some of its greenness, dampen the surface with water.

CONSUMPTION

4.3 to 6.6m² per liter. Consumption can vary greatly depending on the type of spray nozzle.

PACKAGING

UltraCure AB is available in 200 liter drum

GENERAL INFORMATION

Shelf Life 12 months from date of manufacture when stored under warehouse conditions in original unopened packing. Extreme temperature/humidity may reduce shelf life.

HEALTH and SAFETY

Gloves, goggles & suitable mask must be worn.

TECHNICAL SERVICE

Philippine SkyBird Industrial Corp. Services are available on request for on-site support to assist in the correct use of its products.